

Plazma 2200

■ Acrylic Putty



Description

Ready to use acrylic copolymer latex base putty.

Features : Ease of application, good wetting and high workability.

Can also be used as an undercoat upon thinning .

It is not a finish coat, and should always be covered with either water or solvent based paint within one week of application.

Uses : for filling small holes and fine cracks, and for making surface even on Interior dry walls, plaster and concrete surfaces.

Technical Data

Color	White
Appearance	Smooth, Matt
Spreading Rate	1.25-1.75 sq.m/kg per coat, however it depends on surface roughness.
Drying Time	at 25°C and 60% R.H
- Superficial Dryness Time	30-40 mins.
- Tack Free	2-3 hours
- Recoat Ability	3 hours
Note	The drying time increases as the thickness of the putty layer is more than 200 microns.

Plazma 2200



■ Acrylic Putty

Application Information

Recommended thinner : Tap water.

Surface preparation : Surface should be clean, dry, free of dust, grease and oils.

Wash with warm soapy water ,then rinse with fresh water.

Glossy surfaces should be dulled by sanding.

Recommended system: Porous surface should be sealed with sealer clear or white (Sealer Strong 1100) As putty apply one-two coats according to surface condition to assure smooth surface. AS Undercoat, thin to workable consistency then apply one-two coats of Sab Coatings water-based paints.

Application Method: With filling knife or spatula

Application Remarks:

- Not to be applied at temperature below 5 °c

STORAGE INFORMATION

SHELF LIFE : 12 months as well ventilated storage area, a way of direct sun.

weight : Printed on plastic containers.

Safety Information

- Do not take internally

- Close container after each use

(KEEP OUT OF REACH OF CHILDREN)

■ The information provided about the product is the result of our own laboratory and practical experience. Since the product is often used under different conditions. We cannot guarantee anything but the quality of the product itself. For more inquiries, please contact the technical office